



Care & Maintenance Instructions

(Revised 2018)

Thank you for your purchase, we appreciate your business! This data sheet explains how to extend the life of your new CRYSTALCLEAR enclosure panels. Detailed care and maintenance information are also available on our website, <http://www.strataglass.com>.

- To properly clean and maintain your CRYSTALCLEAR products we recommend using [Strataglass Protective Cleaner](#) and [Strataglass Protective Polish](#). Both products are by [IMAR](#) and available through your CRYSTALCLEAR provider or favorite retail marine store. Use of non-authorized cleaners or protectants may damage the CRYSTALCLEAR vinyl.
- **ALWAYS** use **Strataglass Protective Cleaner** to *immediately* remove harmful liquids, creams, chemicals or sprays that come in contact with the CRYSTALCLEAR surface.

Rinsing the CRYSTALCLEAR Curtains: Each time you use the boat, flush the CRYSTALCLEAR curtains thoroughly with clear water to rinse away any salt or environmental abrasives. Air dry or use a high quality chamois or a microfiber towel.

Cleaning the CRYSTALCLEAR Curtains: (every 1-2 weeks) Spray the **Strataglass Protective Cleaner** directly on the inside and outside surface of the CRYSTALCLEAR or onto a soft cotton or micro fiber cloth. Gently wipe the CRYSTALCLEAR surface to clean. If necessary, buff dry with another dry clean cloth. **Strataglass Protective Cleaner** should *always* be on hand for emergency spot cleaning of any harmful liquids, creams, chemicals or sprays that may come in contact with the STRATAGLASS surface.

Polishing the CRYSTALCLEAR Curtains: (every 1-2 months) this is the most important maintenance procedure to extend the life of the curtains. Make sure the CRYSTALCLEAR product is clean and dry. Apply a light coat of **Strataglass Protective Polish**, inside and out, with small, light circular motions using a soft cotton cloth or applicator pad. Allow the polish to quickly dry. Lightly buff with a dry soft cotton or micro fiber cloth to a sparkling smooth shine. The **Strataglass Protective Polish** should be applied every 1-2 months, especially when the enclosure is new. Over time, with multiple applications, the polish will build up a protective barrier.

Note to the Fabricator: Upon project completion, we recommend using **Strataglass Protective Cleaner** to thoroughly clean the enclosure panels followed by a thorough application of **Strataglass Protective Polish**, both inside and out, as a final step in the fabrication process. This will establish the first basecoat of protection and promote watershed.

Note to the Owner: New clear vinyl products are soft and easily impressionable. We recommend that new CRYSTALCLEAR enclosures panels should be in the installed position and fastened securely to the boat as much as possible. If the new curtains need to be removed and stacked, the enclosure panels should be carefully interleaved with a soft fabric such as a bed sheet. Clear vinyl will inherently strengthen over time and become less impressionable. When the boat is not in use, always close and fasten the CRYSTALCLEAR enclosure panels in place to prolong the life of your curtains and maintain clarity.

- **NEVER**
 - Use Windex, Rain-X, Pledge, Plexus, Simple Green, Orpine or any other harsh cleaner to clean CRYSTALCLEAR products.
 - Use a car wax or any kind of wash and wax to protect CRYSTALCLEAR products.
 - Use cleaners, polishes, scratch removers, or any products intended for commercial grade vinyl or plastic. This may damage the CRYSTALCLEAR.

2968 Ravenswood Road, #107 Fort Lauderdale, Florida 33312 USA
(800) 581-5801 (954) 581-2221
www.strataglass.com