

Safety Data Sheet

Section 1 – Identification

Identity/Product Name: Canvak Canvas Preservative

Chemical Family: Aliphatic Hydrocarbon Compound

Manufacturer's Name: Buckeye Fabric Finishing Company
1260 East Main Street
Coshocton, Ohio 43812

24 hr. Emergency (Chemtrec) 1-800-424-9300
Information Telephone No: (740) 622-3251

Recommended use: For revitalizing canvas tarpaulin, not recommended for synsetics.

Section 2 – Hazard(s) Identification

WHMIS Class B-3: Combustible liquid with a flash point between 37.8 C (100 F) and 93.3 C (200F)



Warning

Section 3 – Composition/Information on Ingredients

Canvak Canvas Preservative is a mixture of chemicals, the identities of which are withheld as a trade secret pursuant to 29 C.F.R. Sections 1910.1200(g)(2)(ii) and (i)(1)(i-iv).

Section 4 – First-aid Measures

If on skin: Remove contaminated clothing. Wash exposed area with soap and water. Launder contaminated clothing before reuse. If symptoms persist, seek medical attention.

If in eyes: If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes for at least 20 minutes while holding eyelids apart and seek immediate medical attention.

If swallowed: Do not induce vomiting, keep person warm, quiet, and get medical attention. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal.

If breathed: If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped give artificial respiration. Keep person warm, quiet and get immediate medical attention.

Section 5 – Fire-fighting Measures

Extinguishing Media: use dry chemical (BC) or Carbon Dioxide (CO2) fire extinguisher to extinguish

Special Fire Fighting Procedure: Self-contained breathing equipment

Section 6 – Accidental Release Measures

Steps to be taken in case material is released or spilled: Avoid uncontrolled releases. Contain spilled material. Transfer to secure container. Use absorbent media if necessary.

Disposal: Dispose according to Federal, State and/or Local regulations.

Section 7 – Handling and Storage

Handling: Avoid open flames.

Storing: Store in a cool, dry, ventilated area.

Section 8 – Exposure Control/Personal Protection

Ventilation: Product typically should be applied outdoors. If applied indoors, local exhaust should be adequate.

Protective Gloves: Nitrile or neoprene gloves

Other Protective Equipment: Safety glasses

Section 9 – Physical and Chemical Properties

Appearance and Odor: Clear, light yellow to "tea" colored liquid with slight hydrocarbon odor

Vapor Pressure (mm Hg.): 5.367 @ 20°C

Boiling point: 365° F

Flash point: between 37.8 C (100 F) and 93.3 C (200F)

Specific Gravity: 0.8072

Viscosity (ASTM) D445): 1.1 cSt

VOC content by weight: < 60%

Section 10 – Stability and Reactivity

Stability: Material is stable

Conditions to Avoid: Heat, flames and sparks

Incompatibility (material to avoid): Strong Oxidizers

Hazardous Decomposition Products: Burning may produce carbon monoxide, carbon dioxide and various hydrocarbons.

Hazardous Polymerization: will not occur

Section 11 – Toxicological Information

Primary Route(s) of Entry: Inhalation, skin contact, ingestion, and eye contact

Effects of Overexposure:

Eye: Exposure to liquid or vapors may cause severe eye irritation. Symptoms may include burning, tearing, redness and swelling.

Skin: Exposure may cause mild irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying, and cracking and skin burns.

Breathing: Excessive inhalation of vapors can cause nasal and respiratory irritation, central nervous system effects including dizziness, weakness, fatigue, nausea, headache and possible unconsciousness, and even death.

Swallowing: Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis, which can be fatal.

Effects of Chronic Overexposure: Overexposure to this material (or its components) has been suggested as a cause of central nervous system effects in humans.

Section 12 – Ecological Information

No Data Available

Section 13 – Disposal Considerations

Disposal: Dispose according to all applicable Federal, State and/or Local regulations. For assistance contact a disposal, recycling and/or waste stream reduction facility.

Section 14 – Transport Information

DOT Shipping: UN1268, Petroleum Distillates n.o.s, (contains mineral spirits), Class B3, PG III

Section 15 – Regulatory Information

Section 313 Compounds: Zinc Compounds 1.9%

California Proposition 65: This product may contain small amounts of chemical known to the state of California to cause cancer or reproductive toxicity. Very small amounts of benzene and/or toluene may be present in one of the compounds containing mineral spirits, but we do not analyze for these or other listed chemicals in our product.

HMIS	
Health	0
Flammability	2
Reactivity	0

Section 16 – Other Information

Date Prepared: 9/9/2013

Disclaimer: The information contained herein is believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.