

Trivantage® Causeway® Warranty

3 Year: Limited Product Warranty.

This warranty applies to the original purchaser of Causeway fabric and is subject to inspection. During the three-year limited warranty term, if the Causeway product becomes unserviceable due to loss of strength or color from normal usage and exposure, any warranty claim may be eligible for replacement product.

Warranty Guidelines

For a warranty claim, Trivantage requires a sample of the product in question and must be given the right to inspect the product.

Damage resulting from the following is not covered under warranty:

- Improper installation or cleaning;
- Excessive staining due to gear lubricant, ink, lipstick, motor oil, iodine, betadine, tomato-based sauces or sun lotion;
- Discoloration due to the presence of amines or mildew growth in adjoining foam or adhesives; or
- Normal wear and tear.

Warranties apply only to the top side of the product and do not apply to other items that may be present in an installation (e.g. foam, sewing thread, plywood, etc.).

The warranty period begins from the date an original equipment manufacturer installed the product, or the date the product was sold to an aftermarket manufacturer. Trivantage may, in its discretion, recommend remedial methods, such as professional cleaning or repair to be done at the consumer's expense, in lieu of replacing the product.

To get warranty service, please contact the dealer or retailer from whom the product was purchased. The original purchaser will contact the manufacturer of the item purchased who will then contact Trivantage.

Trivantage.com
800-786-1876

TRIVANTAGE® AND CAUSEWAY® ARE REGISTERED TRADEMARKS OF GLEN RAVEN, INC. All Rights Reserved.

September 15, 2021

Product Use Recommendations

- The product and any substructure should be constructed so that it will dry quickly if it becomes wet.
- Boat owners should cover their boats when not in use and allow venting to avoid trapping moisture.
- Boat owners should refrain from storing or leaving wet items on the product.
- Seams should be as water-tight as possible.
- Product should be cleaned frequently and properly.
- Foam, if used, should be treated to inhibit fungal growth.
- Plywood, if used, should be treated to be mildew and rot resistant