

Fast Fabric Adhesives

Application Instructions & Best Practices

BEFORE YOU BEGIN: It's always recommended that fabricators test the use of these adhesives on some scrap material and learn best practices before using on a project.

RECOMMENDED APPLICATIONS: Liquid RF adhesives are engineered and designed for use on our popular Laminated Awning vinyls like Patio 500®, Weblon® Coastline Plus®, Weather-Chek®, and more. The Liquid RF is a very fast acting adhesive and is great for completing field repairs and adding rafter bands on large awnings.

HOW TO USE

- Apply a thin layer of Liquid RF between 2 layers of laminated vinyl and apply pressure until bond occurs.
- Liquid RF is a moisture activated adhesive, and relative humidity and conditions may impact cure time.
- In normal applications, the adhesive has a cure time of about 5 – 10 seconds. Very dry conditions or a heavy application of adhesive may increase the cure time.



HOW TO USE: RAFTER BAND INSTALLATION

- Applying rafter bands in the field with Fast Fabric Adhesives can eliminate lots of precise field measurements and ensure that the rafter bands are exactly where they need to be quickly and easily.
- To install these in the field, simply build the cover and install on the frame and then position the rafter bands on the rafters.
- Push up on the cover and apply a thin bead of Liquid RF with a caulk gun and let the fabric come in contact with the rafter band to create a strong permanent bond.



FIND THE RIGHT SIZE:

- Our 300 ml cartridge fits in a standard caulk tube and is perfect for installing rafter bands on Laminated Vinyl awning covers
- The 400 ml squeeze bottle works great for adding patches or reinforcements.

