

TAPE-CRAFT

MANUFACTURER OF NARROW FABRICS

MATERIAL SAFETY DATA SHEET

MANUFACTURER NAME, ADDRESS, AND TELEPHONE NUMBER:

TAPE-CRAFT, 200 Tape Craft Drive, Oxford, AL 36203, (800) 521-1783

DATE OF PREPARATION: Created on 1/07/02, Rev. 01/08/08

CONTACT: Tim Phillips/John Jennings

TAPE CRAFT MATERIAL IDENTITY: Natural Cotton Webbing

MATERIAL DESCRIPTION: Textile products containing natural cotton (not bleached or dyed) including fibers, yarns and wastes.

HAZARDOUS INGREDIENTS		SECTION II		
CHEMICAL NAME, COMMON NAME(S):	CAS NUMBER:	% BY WT.:	OSHA PEL:	ACGIH TLV:
Coton dust			200-1000 mg/m ³	200 mg/m ³
PHYSICAL DATA		SECTION III		
Boiling Point °F °C (or range) Not Applicable	Specific Gravity (H₂O=1): Not Applicable		Vapor Pressure (mmHg): Not Applicable	
Percent Volatile By Volume (%) : Not Applicable	Vapor Density (Air=1): Not Applicable		Evaporation Rate: Not Applicable	
Volatile Organic Compounds: Not Applicable	pH at full strength: Not Applicable		Melting Point °F °C	
Solubility in Water: 1. Negligible	At recommended dilution:		Not Applicable	
	1. Negligible (<0.1%)		4. Appreciable (>10%)	
	2. Slight (0.1-1%)		5. Complete (in all proportions)	
	3. Moderate (1-10%)			
Appearance and Odor: Textile products: no significant odor.				
FIRE AND EXPLOSION HAZARD DATA		SECTION IV		
Flash Point (method used): Does Not Apply	Flammable Limits: Not Applicable		Ignition Temp.: Not Applicable	
	Lel Uel			

Special Fire and Explosion Hazards: Combustion produces carbon dioxide and carbon monoxide: wool or polyacrylic components, if present, will produce hydrogen cyanide.

Extinguishing Media: Water or any suitable source

Special Firefighting Procedures: Wear a self contained breathing apparatus required for toxic gases and oxygen depletion.



