



## STYLE 7200R / 7250R

RESIDENTIAL

7200R - BLACKOUT FABRIC  
7250R - LIGHT-FILTERING FABRIC

---

WEAVING  
EXCELLENCE  
WITH  
INNOVATION



		SOLAR OPTICAL PROPERTIES				SHGC/G VALUE g-tot (glass & blind)	
Code	Color	TS	RS	AS	TV	SINGLE 1/4 CL	INSULATING 1 HA
<b>STYLE 7200R - BLACKOUT</b>							
RB1	Swan	0	71	29	0	0.23	0.19
RB8	Raven	0	70	30	0	0.23	0.20



PRODUCT CERTIFIED FOR  
LOW CHEMICAL EMISSIONS  
UL.COM/GG  
UL 2818



TS = Solar Transmittance  
RS = Solar Reflectance  
AS = Solar Absorptance  
TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass  
1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally  
Zero-Degree Profile Angle

For additional performance values,  
test references and technical  
definitions visit us at [phifer.com](http://phifer.com).





STYLE  
7200R

RB1  
**Swan**

RB2  
**Oyster**

RB3  
**Sail**

RB4  
**Chiffon**

RB6  
**Earl Grey**

RB5  
**Chrome**

RB7  
**Blazer**

RB8  
**Raven**



STYLE  
7250R

RL1  
**Swan**

RL2  
**Oyster**

RL3  
**Sail**

RL4  
**Chiffon**

RL6  
**Earl Grey**

RL5  
**Chrome**

RL7  
**Blazer**

RL8  
**Raven**

# STYLE 7200R / 7250R SPECIFICATIONS

Whether contemporary or traditional, Style 7200R complements any design scheme, combining total light blockage with a neutral yet subtly variegated pattern. Style 7250R offers a light-filtering option, using the same face fabric and pattern of Style 7200R to allow natural light to brighten interior spaces.

These fabrics are suitable for roller shades, Roman shades and panel track systems and are ideal for residential use.

<b>STYLE 7200R FIRE CLASSIFICATION</b>	California Technical Bulletin 117 NFPA 101 (Class B Rating)	IBC Section 803.1.1 (Class B Rating)
<b>STYLE 7250R FIRE CLASSIFICATION</b>	California Technical Bulletin 117 NFPA 101 (Class A Rating)	IBC Section 803.1.1 (Class A Rating)

*Fire classifications are subject to change. Please go to [phifer.com](http://phifer.com) for the most current information.*

<b>BACTERIA AND FUNGAL RESISTANCE</b>	ASTM G21	ASTM E 2180
---------------------------------------	----------	-------------

<b>ENVIRONMENTAL CERTIFICATION</b>	GREENGUARD	GREENGUARD Gold
	Certified to these standards for low chemical emissions into indoor air during product usage	

<b>SAFE USE</b>	ANSI/WCMA A 100.1-2007 for lead content RoHS Compliant	US Consumer Product Safety Commission Section 101
-----------------	-----------------------------------------------------------	---------------------------------------------------

<b>WARRANTY</b>	5-year interior
-----------------	-----------------

<b>UV PROTECTION</b>	SheerWeave sun control fabrics are an effective way to reduce harmful UV rays. Phifer Incorporated is a proud member of the Skin Cancer Foundation's Corporate Council.	
----------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--

<b>CLEANING INSTRUCTIONS</b>	Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility.	
------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--

*Railroading this fabric is not recommended.*

*Colors may vary slightly from swatch samples. All variations are within industry standards.*

STYLE	7200R	7250R
<b>WIDTHS</b>	118" 300 cm	118" 300 cm
<b>ROLL LENGTH</b>	22 Linear Yards 20 Linear Meters	22 Linear Yards 20 Linear Meters
<b>COMPOSITION</b>	100% Polyester with Acrylic Foamed Backing	100% Polyester with Acrylic Coating
<b>MESH WEIGHT</b>	11.06 oz/yd <sup>2</sup> 375 g/m <sup>2</sup>	6.19 oz/yd <sup>2</sup> 210 g/m <sup>2</sup>
<b>FABRIC THICKNESS</b>	0.024 in 0.60 mm	0.018 in 0.45 mm
<b>OPENNESS FACTOR</b>	Opaque	Light-filtering
<b>ACOUSTICAL VALUE</b>	NRC .00 / SAA .02	NRC .50 / SAA .50

**PHIFER**  
INCORPORATED

P. O. Box 1700 • Tuscaloosa, Alabama 35403-1700 USA  
Phone: 205.345.2120 • FAX: 205.391.0799  
Toll Free USA/Canada: 1.800.221.5497  
[phifer.com](http://phifer.com) • ISO Registered



© SheerWeave is a registered trademark of PHIFER INCORPORATED.  
™ UL, the UL logos and the UL mark are trademarks of UL LLC.  
Photo courtesy of Blind Design, South Africa  
© PHIFER INCORPORATED V24 022924 3038201