



JET 550

FRONTLIT 17 oz/yd²

APPLICATIONS

- ONE SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- INDOOR / OUTDOOR: billboards / banners/ signage / POS / pole banners

PRODUCT PACKAGING

| | | |
|-------------------|-------------------------------------|------------------------|
| WIDE FORMAT | 30" / 42" / 54" 64" / 98" / 126" | Rolls of: 98' (30 lm) |
| SUPER WIDE FORMAT | 98" / 109" / 126" | Rolls of: 197' (60 lm) |

PRODUCT CHARACTERISTICS

| | |
|------------------------------------|---|
| WEIGHT | 17 oz/yd ² (560 g/m ²) |
| BASE CLOTH | High tenacity polyester 1100 Dtex |
| COATING | PVC coating System LOWICK |
| FINISH | Satin Inkjet lacquer One side |
| COLOUR | White 7325 |
| THICKNESS | 19 mils (0.47 mm) |
| TRANSLUCENCY XPT 54 199 | 6 % |
| TENSILE STRENGTH NF EN ISO 1421 | 240 x 228 lbs / inch (210 / 200 daN) |
| TEAR STRENGTH DIN 53363 | 56 x 45 lbs (25 / 20 daN) |
| TEMPERATURE STABILITY | -30°C to +70°C -22°F to +158°F |
| ADHESION NF EN ISO 2411 | 0,8 lbs /inch |
| FIRE RETARDENT | DIN 75 200 NFPA 701 |

Average values +/- 10%



SYSTEM
LOWICK



Certified for
HP Latex Inks



Company with management system certified by DNV-GL
ISO 9001 · ISO 14001



www.dickson-coatings.com
www.evergreen-fabrics.com