



# JET 550

## FRONTLIT 17 oz/yd<sup>2</sup>

### APPLICATIONS

- ONE SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- INDOOR / OUTDOOR: billboards / banners / signage / POS / pole banners

### PRODUCT PACKAGING

WIDE FORMAT	30" / 42" / 54" / 64" / 98" / 126"	Rolls of: 98' (30 lm)
SUPER WIDE FORMAT	98" / 109" / 126"	Rolls of: 197' (60 lm)

### PRODUCT CHARACTERISTICS

WEIGHT	17 oz/yd <sup>2</sup> (560 g/m <sup>2</sup> )		
COATING	PVC coating System LOWICK	Base cloth	High tenacity polyester 1100 Dtex
COLOUR	White 7325	Finish	Satin Inkjet lacquer One side
THICKNESS	19 mils (0.47 mm)	Translucency XP T 54 199	6 %
TENSILE STRENGTH NF EN ISO 1421	240 x 228 lbs / inch (210 / 200 daN)	Tear strength DIN 53363	56 x 45 lbs (25 / 20 daN)
TEMPERATURE STABILITY	-30°C to +70°C -22°F to + 158°F	Adhesion NF EN ISO 2411	0,8 lbs /inch
FIRE RETARDENT	DIN 75 200 NFPA 701		

Average values +/- 10%



Company with management system certified by DNV-GL  
ISO 9001 · ISO 14001

[www.dickson-coatings.com](http://www.dickson-coatings.com)  
[www.evergreen-fabrics.com](http://www.evergreen-fabrics.com)