



LACOPAC

BLACKOUT 20 oz/yd²



FLAME RETARDANT



NO CURLING

APPLICATIONS

- BOTH SIDE PRINTING
- DIGITAL PRINTING: solvent / eco-solvent / UV and Latex inks
- INDOOR COMMUNICATION: signage / banners / POS / hanging banners

PRODUCT PACKAGING

WIDE FORMAT	40" / 54" / 122"	Rolls of: 98' (30 lm)
SUPER WIDE FORMAT	122"	Rolls of: 197' (60 lm)

PRODUCT CHARACTERISTICS

WEIGHT	20 oz/yd ² (680 g/m ²)		
COATING	PVC coating System LOWICK	Base cloth	High tenacity polyester 550 Dtex
COLOUR	White 7326	Finish	Satin inkjet lacquer Both side
THICKNESS	19 mils (0.49 mm)	Translucency XP T 54 199	0 %
TENSILE STRENGTH NF EN ISO 1421	205 x 171 lbs / inch (180 / 150 daN)	Tear strength DIN 53363	45 x 45 lbs (20 / 20 daN)
TEMPERATURE STABILITY	-30°C to +70°C -22°F to +158°F	Adhesion NF EN ISO 2411	0,8 lbs /inch
FIRE RETARDENT	M2 / B1 B-s2-d0 (EN 13 501-1) NFPA 701		

Average values +/- 10%



Company with management system certified by DNV-GL
ISO 9001 · ISO 14001

www.dickson-coatings.com
www.evergreen-fabrics.com