

Voyager is an expanded vinyl coated fabric with the industry-leading **PreFixx** protective finish and is designed for use in marine and other exterior environments.

## Industries & Markets

- Marine

## End-Use Applications

- Coated Fabrics for Boats and Personal Watercraft

## Physical Specifications

Weight (CFFA-700d)	30 oz/lin yd [20 oz/yd <sup>2</sup> ]
Weight, Metric (CFFA-700d)	850 g/lin m [567 g/m <sup>2</sup> ]
Width (CFFA-700a)	54 in. [137 cm]
Face Composition	PVC
Backing Description	Filament Polyester Knit
Roll Size	40 lin yd [37 lin m]
Emboss Level	Light
Shipping Weight/ Roll	75 lb [34 kg]

## Flame, Smoke & Toxicity

Meets or exceeds the following:

- Cal Tech 117-2013 Sec 1
- BIFMA - Class A
- UFAC Fabric, Class 1
- AB 2998

## Performance Features

Protective Finish	PreFixx
Use	Indoor/Outdoor
QUV hours (minimum)	650
Adhesion #/in., min (CFFA-3)	3 Warp, 3 Fill
Tensile Strength #, min (CFFA-17)	85 Warp, 75 Fill
Tack Strength #, min (CFFA-14)	35 Warp, 30 Fill
Trap Tear Strength #, min (CFFA-16c)	20 Warp, 20 Fill
Wyzenbeek Abrasion (CFFA-1a)	1,300,000 Cotton Duck (double rubs)
Blocking (CFFA-4 No. 1)	Pass
W-Flex - 25,000 cycles (CFFA-10)	Pass
Crocking Resistance - 20 cycles no stain (CFFA-7)	Pass
Biocompatibility Certified ISO 10993-13	Pass
Fungal Resistance (ASTM-G-21)	Pass
Cold Crack (CFFA-6a)	-20 °F [-29 °C]
Compatible with Disinfectants	Yes. See Chem Resistance Tech Bulletin for more information.
Bleach-Safe	Yes, 10% Bleach Solution

Revision Date: 17-Mar-20

**Note: Due to possible variances in your computer monitor, the colors and patterns displayed may vary slightly from the actual product. Customers should always obtain and compare actual samples before specifying.**



All OMNOVA products and services are offered and sold subject to the OMNOVA standard terms and conditions of sale agreement set forth at [www.omnova.com](http://www.omnova.com)

Trademarks are property of OMNOVA Solutions Inc. unless otherwise noted.

©2020 OMNOVA Solutions Inc.