

Safety Data Sheet



Section 1: Identification

Product identifier

Product Name

- **303 Fabric Guard**

Synonyms

- 588055

Product Code

- 130606; 30601; 30602; 30603; 30604; 30604CSR; 30605; 30605CSR; 30606; 30606CSR; 30607; 30616; 30618; 30618BD; 30618CSR; 30674

Relevant identified uses of the substance or mixture and uses advised against

Recommended use

- Product is used on recommended materials to create water repellency

Restrictions on use

- Read and follow label directions for product use, safety warnings and hazards

Details of the supplier of the safety data sheet

Manufacturer

- Gold Eagle Co.
4400 S. Kildare Avenue
Chicago, IL 60632-4372
United States
<http://www.goldeagle.com/>

Telephone (General) • 773-376-4400

Emergency telephone number

Manufacturer

- 1-800-535-5053 - (INFOTRAC #22283)

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012

- Flammable Liquids 3
Acute Toxicity Oral 4
Aspiration 1
Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects

Label elements

OSHA HCS 2012

DANGER



Hazard statements

- Flammable liquid and vapour
Harmful if swallowed
May be fatal if swallowed and enters airways
May cause drowsiness or dizziness

Precautionary statements

- Prevention** • Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
 Keep container tightly closed.
 Ground and/or bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing mists, vapours, and/or spray.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.

- Response** • In case of fire: Use appropriate media for extinction.
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 Call a POISON CENTER or doctor/physician if you feel unwell.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 Rinse mouth.
 Do NOT induce vomiting.

- Storage/Disposal** • Store in a well-ventilated place. Keep container tightly closed.
 Keep cool.
 Store locked up.
 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Other hazards

OSHA HCS 2012

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Section 3 - Composition/Information on Ingredients

Substances

- Material does not meet the criteria of a substance.

Mixtures

Composition				
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive
Distillates (petroleum), hydrotreated light	CAS:64742-47-8	0% TO 92%	NDA	OSHA HCS 2012: Flam. Liq. 4; Asp. Tox. 1; STOT SE 3: Narc.
Mineral spirits	NDA	0% TO 5%	NDA	OSHA HCS 2012: Not Classified
Acetic acid, butyl ester	CAS:123-86-4	0% TO 2.4%	Ingestion/Oral-Rat LD50 • 10768 mg/kg Inhalation-Rat LC50 • 390 ppm 4 Hour(s) Skin-Rabbit LD50 • >17600 mg/kg	OSHA HCS 2012: Flam. Liq. 2; Skin Irrit. 2; Eye Irrit. 2B; STOT SE 3: Narc.; STOT SE 3: Resp. Irrit. (Inhl)
Solvent naphtha (petroleum), medium aliph.	CAS:64742-88-7	1.7%	NDA	OSHA HCS 2012: Flam. Liq. 3; Asp. Tox. 1
Fluorinated acrylic copolymer	NDA	0% TO 1.6%	NDA	OSHA HCS 2012: Not Classified

Section 4: First-Aid Measures

Description of first aid measures

- Inhalation**
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.
- Skin**
- IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
- Eye**
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- Ingestion**
- Do NOT induce vomiting. Get medical attention immediately.

Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

- Notes to Physician**
- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

- Suitable Extinguishing Media**
- Use carbon dioxide, dry chemical, foam and/or water fog.

- Unsuitable Extinguishing Media**
- No data available

Special hazards arising from the substance or mixture

- Unusual Fire and Explosion Hazards**
- Flammable; may be ignited by heat, sparks or flames. Containers may explode when heated. Vapor explosion hazard indoors, outdoors or in sewers. Many liquids are lighter than water. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Runoff to sewer may create fire or explosion hazard. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

- Hazardous Combustion Products**
- No data available

Advice for firefighters

- Structural firefighters' protective clothing will only provide limited protection. Wear positive pressure self-contained breathing apparatus (SCBA). Move containers from fire area if you can do it without risk. LARGE FIRES: Cool containers with flooding quantities of water until well after fire is out.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

- Personal Precautions**
- Do not walk through spilled material. Use appropriate Personal Protective Equipment (PPE) Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures

- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. LARGE SPILL: Consider initial downwind evacuation for at least 300 meters (1000 feet) ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

Environmental precautions

- Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up**Containment/Clean-up Measures**

- Stop leak if you can do it without risk. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors. All equipment used when handling the product must be grounded. LARGE SPILLS: Dike far ahead of liquid spill for later disposal. LARGE SPILLS: Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Section 7 - Handling and Storage**Precautions for safe handling****Handling**

- Use only in well ventilated areas. Avoid contact with heat and ignition sources. Take precautionary measures against static charges. Do not use sparking tools. All equipment used when handling the product must be grounded. Agitate contents of container before using. Do not aerosolize this product. Inhalation of this product may cause severe illness or death. Avoid breathing vapor or spray mist. Wear a respirator and use proper ventilation. Avoid contact with eyes or skin. Wear glasses or goggles, gloves and other protective clothing. Use the proper equipment. This includes: exhaust fan, respirator with organic vapor cartridge, glasses or goggles, gloves and protective clothing. Before you start application, set up cross ventilation, open doors and windows, place a fan blowing out of a window or door to increase exhaust. Remove all people and animals from the exposure area. All personnel in the exposure area should wear a proper fitting respirator with organic vapor cartridge. Turn off air conditioner or heating units and remove all ignition sources. After spraying, solvent will continue to evaporate, so you must do the following until the solvent vapor concentration is below 300 ppm (about 30-60 minutes): Continue cross ventilation. Keep people and animals out of the spray area. Continue to wear respirators in the spray area. Do not expose the treated fabric to open flame or other ignition sources (such as matches or cigarette lighters). Avoid contamination of tobacco products. Wash hands thoroughly before smoking. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

Conditions for safe storage, including any incompatibilities**Storage**

- Store in a tightly closed container. Store in a well-ventilated place. Store away from oxidizing agents, sources of heat, direct sunlight or rain. No smoking in area of storage.

Section 8 - Exposure Controls/Personal Protection**Control parameters**

Exposure Limits/Guidelines				
	Result	ACGIH	NIOSH	OSHA
Acetic acid, butyl ester (123-86-4)	TWAs	150 ppm TWA	150 ppm TWA; 710 mg/m ³ TWA	150 ppm TWA; 710 mg/m ³ TWA
	STELs	200 ppm STEL	200 ppm STEL; 950 mg/m ³ STEL	Not established

Exposure controls

Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use only appropriately classified electrical equipment.

Personal Protective Equipment

Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

- Wear chemical splash safety goggles.

Skin/Body

- Wear appropriate gloves.

Environmental Exposure Controls

- Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow best practice for site management and disposal of waste.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

STEL = Short Term Exposure Limits are based on 15-minute exposures

NIOSH = National Institute of Occupational Safety and Health

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

OSHA = Occupational Safety and Health Administration

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	Clear liquid with a banana fragrance.
Color	Clear	Odor	Banana
Odor Threshold	No data available		
General Properties			
Boiling Point	> 150 C(> 302 F)	Melting Point/Freezing Point	No data available
Decomposition Temperature	No data available	pH	No data available
Specific Gravity/Relative Density	= 0.85 Water=1	Water Solubility	Negligible < 0.1 %
Viscosity	3 Centistoke (cSt, cS) or mm ² /sec @ 40 C(104 F)		
Volatility			
Vapor Pressure	0.5 mmHg (torr)	Vapor Density	5.3 Air=1
Evaporation Rate	< 0.1 n-Butyl Acetate = 1	VOC (Wt.)	100 %
VOC (Vol.)	100 %	Volatiles (Wt.)	100 %
Volatiles (Vol.)	100 %		
Flammability			
Flash Point	122 F(50 C) CC (Closed Cup)	UEL	5.5 %
LEL	0.6 %	Autoignition	No data available
Flammability (solid, gas)	No data available		
Environmental			
Octanol/Water Partition coefficient	No data available		

Section 10: Stability and Reactivity

Reactivity

- No dangerous reaction known under conditions of normal use.

Chemical stability

- Stable under normal temperatures and pressures.

Possibility of hazardous reactions

- Hazardous polymerization will not occur.

Conditions to avoid

- Keep away from heat, sparks, and flame. Incompatible materials.

Incompatible materials

- Strong alkalis, acids, and oxidizers.

Hazardous decomposition products

- Thermal decomposition may include irritating vapors and carbon oxides (CO, CO₂)

Section 11 - Toxicological Information

Information on toxicological effects

		Components
Solvent naphtha (petroleum), medium aliph. (1.7%)	64742-88-7	Multi-dose Toxicity: Inhalation-Mouse TCLo • 2200 mg/m ³ 6 Hour(s) 16 Day(s)-Intermittent; Liver:Changes in liver weight; Reproductive Effects:Paternal Effects:Spermatogenesis; Inhalation-Rat TCLo • 550 mg/m ³ 91 Day(s)-Intermittent; Kidney, Ureter, and Bladder:Changes in tubules (including acute renal failure, acute tubular necrosis); Kidney, Ureter, and Bladder:Other changes; Inhalation-Rat TCLo • 550 mg/m ³ 2 Year(s)-Intermittent; Endocrine:Other changes; Endocrine:Tumors; Inhalation-Rat TCLo • 550 mg/m ³ 6 Hour(s) 16 Day(s)-Intermittent; Kidney, Ureter, and Bladder:Other changes in urine composition; Kidney, Ureter, and Bladder:Changes in kidney weight; Reproductive Effects:Paternal Effects:Spermatogenesis
Acetic acid, butyl ester (0% TO 2.4%)	123-86-4	Acute Toxicity: Ingestion/Oral-Rat LD50 • 10768 mg/kg; Behavioral:Somnolence (general depressed activity); Lungs, Thorax, or Respiration:Other changes; Liver:Other changes; Skin-Rabbit LD50 • >17600 mg/kg; Irritation: Eye-Rabbit • 100 mg • Moderate irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Moderate irritation; Multi-dose Toxicity: Inhalation-Rat TCLo • 1500 ppm 6 Hour(s) 13 Week(s)-Intermittent; Behavioral:Somnolence (general depressed activity); Nutritional and Gross Metabolic:Gross Metabolite Changes:Weight loss or decreased weight gain; Inhalation-Rat TCLo • 1500 ppm 6 Hour(s) 13 Week(s)-Continuous; Behavioral:Somnolence (general depressed activity); Behavioral:Food intake (animal); Nutritional and Gross Metabolic:Gross Metabolite Changes:Weight loss or decreased weight gain; Reproductive: Inhalation-Rat TCLo • 1500 ppm 7 Hour(s)(7-16D preg); Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus); Reproductive Effects:Specific Developmental Abnormalities:Musculoskeletal system; Inhalation-Rat TCLo • 1500 ppm (6-20D preg); Reproductive Effects:Effects on Embryo or Fetus:Fetotoxicity (except death, e.g., stunted fetus)

GHS Properties	Classification
Respiratory sensitization	OSHA HCS 2012 • Data lacking
Serious eye damage/Irritation	OSHA HCS 2012 • Data lacking
Acute toxicity	OSHA HCS 2012 • Acute Toxicity - Oral 4
Aspiration Hazard	OSHA HCS 2012 • Aspiration 1
Carcinogenicity	OSHA HCS 2012 • Data lacking
Skin corrosion/Irritation	OSHA HCS 2012 • Data lacking
Skin sensitization	OSHA HCS 2012 • Data lacking
STOT-RE	OSHA HCS 2012 • Data lacking
STOT-SE	OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects

Toxicity for Reproduction	OSHA HCS 2012 • Data lacking
Germ Cell Mutagenicity	OSHA HCS 2012 • Data lacking

Potential Health Effects

Inhalation

- Acute (Immediate)**
 - May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.
- Chronic (Delayed)**
 - No data available.

Skin

- Acute (Immediate)**
 - May cause mild irritation.
- Chronic (Delayed)**
 - No data available.

Eye

- Acute (Immediate)**
 - May cause mild irritation.
- Chronic (Delayed)**
 - No data available.

Ingestion

- Acute (Immediate)**
 - Harmful if swallowed. Material may be aspirated into lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.
- Chronic (Delayed)**
 - No data available.

Key to abbreviations

LD = Lethal Dose

TC = Toxic Concentration

Section 12 - Ecological Information

Toxicity

- Non-mandatory section - information about this substance not complied for this reason.

Persistence and degradability

- Non-mandatory section - information about this substance not complied for this reason.

Bioaccumulative potential

- Non-mandatory section - information about this substance not complied for this reason.

Mobility in Soil

- Non-mandatory section - information about this substance not complied for this reason.

Other adverse effects

- Non-mandatory section - information about this substance not complied for this reason.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class(es)	Packing group	Environmental hazards
DOT	NDA	Limited Quantity	NDA	NDA	NDA

Special precautions for user • None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code • No data available

Section 15 - Regulatory Information**Safety, health and environmental regulations/legislation specific for the substance or mixture**

SARA Hazard Classifications • Acute, Fire

Inventory		
Component	CAS	TSCA
Acetic acid, butyl ester	123-86-4	Yes
Distillates (petroleum), hydrotreated light	64742-47-8	Yes
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Yes

United States**Labor****U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals**

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

Environment**U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants**

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - CAA (Clean Air Act) - Accidental Release Prevention - Flammable Substances

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - CAA (Clean Air Act) - Accidental Release Prevention - Toxic Substances

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl acetate)
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - CWA (Clean Water Act) - Hazardous Substances

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	(listed under Butyl acetate)
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - CWA (Clean Water Act) - Toxic Pollutants

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

United States - California**Environment****U.S. - California - Proposition 65 - Carcinogens List**

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

• Distillates (petroleum), hydrotreated light	64742-47-8	Not Listed
• Acetic acid, butyl ester	123-86-4	Not Listed
• Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed

Section 16 - Other Information**Revision Date**

- 14/September/2015

Preparation Date

- 01/July/2012

Disclaimer/Statement of Liability

- Information presented herein is believed to be factual, as it has been derived from the works and opinions of persons believed to be qualified experts. However, nothing contained in this information is to be taken as warranty or representation for which the Gold Eagle Co. bears legal responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.

Key to abbreviations

NDA = No Data Available