## Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

## **U.S. Department of Labor**



Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List)	Note: Blank spaces are not permitted. If any item is not
RETREAT	applicable, or no information is available, the space must be marked to indicate that.

## **Section I**

Nassimi LLC	Emergency Telephone Number 212-643-8080
SEVEN PENN PLAZA 370 Seventh Ave	Telephone Number for Information 212-643-8080
Suite 1600	Date Prepared 9/17/2009
New York, NY 10001	Signature of Preparer (optional)

# Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
PVC Resin				
Plasticizers (Phthalate Free)				
Stabilizer				
Pigment				
Modifier, Filler				
Surface Coating Agent				
1				

## **Section III - Physical/Chemical Characteristics**

Boiling Point	N/A	Specific Gravity ( $H_2O = 1$ )		1.20-1.50
Vapor Pressure (mm Hg)	N/A	Melting Point		N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)		N/A
Solubility in Water Not Soluble			Decomposition Temperature 500°F (260°C)	
Appearance and Odor Solid Flexible Material-Mild Characteristic Odor				

## Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) 260°C-390°C(ASTM D-1929)	Flammable Limits N/A	LEL N/A	UEL N/A	
Extinguishing Media Water, Dry Chemical Foam, CO <sub>2</sub>				
Special Fire Fighting Procedures Wear self-contained breathing apparatus and protective clothing to prevent contact				
with skin and eyes. Do not breathe toxic gases of combustion.				
Unusual Fire and Explosion Hazards Any Vinyl can be forced to burn by continuous application of intense heat,				
combustion products contain HCL and other toxic gases. Do not breathe fumes.				

(Reproduce locally)

OSHA 174, Sept. 1985

# Section V - Reactivity Data

Stability	Unstable Conditions to Avoid N/A				
	Stable	X			
Incompatibility	(Materials to A	void) N/A			
Hazardous Dec	Hazardous Decomposition or Byproducts N/A				
Hazardous Polymerization	May Occur		Conditions to Avoid N/A		
	Will Not Occur	X			

## Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?		
N/A	No health effects	No health effects	No health effects		
Health Hazards (Acute and Chronic) No health effects are expected					
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?		
N/A	N/A	N/A	N/A		

Signs and Symptoms of Exposure

N/A

#### Medical Conditions Generally Aggravated by Exposure

#### N/A

Emergency and First Aid Procedures

If irritation persists form processing vapor or decomposition products

remove individual from the area.

### Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled N/A

Waste Disposal Method

Use approved disposal method as recommended by state and local agencies.

Precautions to Be taken in Handling and Storing

The products should be stored in room temperature, dry, well-ventilated area, away from

Flammable materials or source of heat and flame.

Other Precautions

Under normal circumstanced of use and handling procedures this product is not considered

to be hazardous.

#### **Section VIII - Control Measures**

Respiratory Pr	otection <i>(Specify Type)</i> None sho	uld be ne	eeded	
Ventilation	Local Exhaust. None should be needed		Special N/A	
	Mechanical (General) Recomr	nended	Other N/A	
Protective Gloves Eye Pr When material is heated			tection Recommended for all industrial workplace	
Other Protective Clothing or Equipment None should be needed				
Work/Hygienio	c Practices		* U.S.G.P.O.: 1986 - 491 - 529/45775	