## Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

## **U.S. Department of Labor**



Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

| IDENTITY (As Used on Label and List) | Note: Blank spaces are not permitted. If any item is not                               |
|--------------------------------------|--|
| VISION                               | applicable, or no information is available, the space must be marked to indicate that. |

## **Section I**

| Nassimi LLC                         | Emergency Telephone Number<br>212-643-8080       |
|-------------------------------------|--|
| SEVEN PENN PLAZA<br>370 Seventh Ave | Telephone Number for Information<br>212-643-8080 |
| Suite 1600                          | Date Prepared<br>9/10/2015                       |
| New York, NY 10001                  | Signature of Preparer (optional)                 |

# Section II - Hazardous Ingredients/Identity Information

| Hazardous Components (Specific     |          | ACGIH | Other Limits |             |
|------------------------------------|----------|-------|--------------|-------------|
| Chemical Identity; Common Name(s)) | OSHA PEL |       | Recommended  | %(optional) |
|                                    |          |       |              |             |
| PVC Resin                          |          |       |              | 40-45       |
|                                    |          |       |              |             |
| Plasticizer                        |          |       |              | 35-40       |
|                                    |          |       |              | 2           |
| Stabilizer                         |          |       |              | 2           |
| Diamont                            |          |       |              | 2 Г         |
| Pigment                            |          |       |              | 3-5         |
| Modifier, Filler                   |          |       |              | 10-15       |
|                                    |          |       |              |             |
| Surface Coating Agent              |          |       |              | 1           |
|                                    |          |       |              |             |
|                                    |          |       |              |             |
|                                    |          |       |              |             |
|                                    |          |       |              |             |
|                                    |          |       |              |             |
|                                    |          |       |              |             |
|                                    |          |       |              |             |

## **Section III - Physical/Chemical Characteristics**

| Boiling Point   | N/A | Specific Gravity (H <sub>2</sub> O = 1) |  | 1.20-1.50 |
|---|-----|---|--|-----------|
| Vapor Pressure (mm Hg)  | N/A | Melting Point                           |  | N/A       |
| Vapor Density (AIR = 1)   | N/A | Evaporation Rate<br>(Butyl Acetate = 1) |  | N/A       |
| Solubility in Water<br>Not Soluble                                      |     |   | Decomposition Temperature<br>500°F (260°C) |           |
| Appearance and Odor<br>Solid Flexible Material-Mild Characteristic Odor |     |   |  |           |

## Section IV - Fire and Explosion Hazard Data

| Flash Point (Method Used)<br>260°C-390°C(ASTM D-1929)  | Flammable Limits<br>N/A | LEL<br>N/A | UEL N/A |  |
|--|-------------------------|------------|---------|--|
| Extinguishing Media<br>Water, Dry Chemical Foam, CO <sub>2</sub>   |                         |            |         |  |
| Special Fire Fighting Procedures<br>Wear self-contained breathing apparatus and protective clothing to prevent contact |                         |            |         |  |
| with skin and eyes. Do not breathe toxic gases of combustion.  |                         |            |         |  |
| Unusual Fire and Explosion Hazards<br>Any Vinyl can be forced to burn by continuous application of intense heat,       |                         |            |         |  |
| combustion products contain HCL and other toxic gases. Do not breathe fumes.   |                         |            |         |  |

(Reproduce locally)

OSHA 174, Sept. 1985

# Section V - Reactivity Data

| Stability                   | Unstable   |   | Conditions to Avoid<br>N/A |  |  |
|-----------------------------|--|---|----------------------------|--|--|
|                             | Stable   | X |                            |  |  |
| Incompatibility             | Incompatibility <i>(Materials to Avoid)</i><br>N/A |   |                            |  |  |
| Hazardous Dec               | Hazardous Decomposition or Byproducts<br>N/A       |   |                            |  |  |
| Hazardous<br>Polymerization | May Occur  |   | Conditions to Avoid<br>N/A |  |  |
|                             | Will Not<br>Occur                                  | X |                            |  |  |

## Section VI - Health Hazard Data

| Route(s) of Entry:<br>N/A  | Inhalation?<br>No health effects | Skin?<br>No health effects | Ingestion?<br>No health effects |  |  |  |
|--|----------------------------------|----------------------------|---------------------------------|--|--|--|
| Health Hazards (Acute and Chronic)<br>No health effects are expected |                                  |                            |                                 |  |  |  |
| Carcinogenicity: NTP? IARC Monographs? OSHA Regulated? N/A N/A N/A   |                                  |                            |                                 |  |  |  |

Signs and Symptoms of Exposure

N/A

#### Medical Conditions Generally Aggravated by Exposure

#### N/A

Emergency and First Aid Procedures

If irritation persists form processing vapor or decomposition products

remove individual from the area.

### Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled N/A

Waste Disposal Method

Use approved disposal method as recommended by state and local agencies.

Precautions to Be taken in Handling and Storing

The products should be stored in room temperature, dry, well-ventilated area, away from

Flammable materials or source of heat and flame.

Other Precautions

Under normal circumstanced of use and handling procedures this product is not considered

to be hazardous.

#### **Section VIII - Control Measures**

| Respiratory Protection (Specify Type)<br>None should be needed  |                                      |        |  |  |
|---|--------------------------------------|--------|--|--|
| Ventilation   | Local Exhaust. None should be needed |        | Special N/A  |  |
|   | Mechanical (General)<br>Recom        | mended | Other N/A  |  |
| Protective Gloves Eye Pro<br>When material is heated            |                                      |        | ection<br>Recommended for all industrial workplace |  |
| Other Protective Clothing or Equipment<br>None should be needed |                                      |        |  |  |
| Work/Hygienio   | Practices                            |        | * U.S.G.P.O.: 1986 - 491 - 529/45775               |  |