



SAFETY DATA SHEET

Issuing Date 01-Feb-2017

Revision Date 01-Feb-2017

Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name RAL1013 Sand/Ivory Aerosol

Other means of identification

Product Code(s) 21443

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Aerosol Spray Paint

Uses advised against No information available

Supplier's details

Supplier Address

Premier Aerosol Packaging, Inc.
7777 Hub Parkway
Valley View, Ohio 44125
TEL: 216-674-1590

Emergency telephone number

Emergency Telephone Number Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Germ Cell Mutagenicity	Category 1B
Reproductive Toxicity	Category 2
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Specific Target Organ Toxicity (Repeated Exposure)	Category 2
Aspiration Toxicity	Category 1
Flammable aerosols	Category 1

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word
Danger
Hazard Statements

- Causes skin irritation
- Causes serious eye irritation
- May cause genetic defects
- Suspected of damaging fertility or the unborn child
- May cause drowsiness or dizziness
- May cause damage to organs through prolonged or repeated exposure
- May be fatal if swallowed and enters airways
-
- Extremely flammable aerosol


Appearance Opaque, Tan

Physical State Liquid.

Odor Solvent

Precautionary Statements
Prevention

- Wash face, hands and any exposed skin thoroughly after handling.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Do not spray on an open flame or other ignition source
- Pressurized container: Do not pierce or burn, even after use.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- If exposed or concerned: Get medical attention/advice
- Specific treatment (see supplemental first aid instructions on this label)

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

Skin

- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation occurs: Get medical advice/attention.
- Take off contaminated clothing and wash before reuse.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Ingestion

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Do NOT induce vomiting.

Storage

- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.
- Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

Harmful to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Acetone	67-64-1	15-40	*
Petroleum gases, liquified, sweetened	68476-86-8	10-30	*
Toluene	108-88-3	10-30	*
Non-hazardous Components	-	10-30	*
Xylene, mixed isomers	1330-20-7	1-5	*
Propylene glycol monomethyl ether acetate	108-65-6	1-5	*
Non-hazardous Components	-	1-5	*
Non-hazardous Components	-	1-5	*
Silica, amorphous, precipitated and gel	112926-00-8	1-5	*
Non-hazardous Components	-	0.1-1	*
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich	68515-48-0	0.1-1	*
Polyethylene	9002-88-4	< 0.1	*
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	< 0.1	*
Carbon black	1333-86-4	< 0.1	*
Ethylbenzene	100-41-4	< 0.1	*
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)	136-52-7	< 0.1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash skin with soap and water. Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. Consult a physician.
Ingestion	Drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately if symptoms occur.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO₂). Halons. Foam.

Unsuitable Extinguishing Media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Will be easily ignited by heat, sparks or flames. Sealed containers may rupture when heated. Ruptured cylinders may rocket. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).

Explosion Data

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

Yes.

Protective Equipment and Precautions for Firefighters

Continue to cool fire exposed cylinders until flames are extinguished. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Deny entry to unauthorized and unprotected personnel. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Ensure adequate ventilation.

Environmental Precautions

Environmental Precautions

Prevent entry into waterways, sewers, basements or confined areas. Avoid release to the environment. Dispose of contents/container to an approved waste disposal plant. See Section 12 for additional Ecological Information. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Methods for Containment

Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

Small spillage: Take up with sand, earth or other noncombustible absorbent material. After cleaning, flush away traces with water. Large spillage: Cover liquid spill with sand, earth or other noncombustible absorbent material. Clean up promptly by sweeping or vacuum.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Do not puncture or incinerate. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. Avoid breathing vapors or mists. Contents under pressure. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Conditions for safe storage, including any incompatibilities

Storage

Keep tightly closed in a dry and cool place. Keep away from direct sunlight. Keep away from heat. Keep container closed when not in use. Store away from incompatible materials and ignition sources. Product should be stored below 120°F

Incompatible Products

Strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
---------------	-----------	----------	------------

Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m ³
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
Xylene, mixed isomers 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-

Appropriate engineering controls**Engineering Measures**

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Safety glasses with side-shields. Face-shield.

Skin and Body Protection

Protective gloves.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical State	Liquid	Appearance	Opaque Tan
Odor	Solvent	Odor Threshold	No information available
<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>	
pH	No data available	None known	
Melting Point/Range	No data available	None known	
Boiling Point/Boiling Range	-1F-340F	None known	
Flash Point	< -20 °F	None known	
Evaporation rate	Faster Than Ether	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limits in Air			
upper flammability limit	16.0		
lower flammability limit	1.0		
Vapor Pressure	No data available	None known	
Vapor Density	Heavier Than Air	None known	
Specific Gravity	.8	None known	
Water Solubility	No	None known	
Solubility in other solvents	100%.	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition Temperature	No data available	None known	
Decomposition Temperature	No data available	None known	
Viscosity	No data available	None known	
Flammable Properties	flammable		
Explosive Properties	No data available		

Oxidizing Properties No data available

Other information

VOC Content (%) 3.21 lbs/gal less federally exempt solvents

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

Nitrogen oxides (NO_x). Carbon monoxide (CO). Carbon dioxide (CO₂).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Vapors may irritate throat and respiratory system. May cause drowsiness and dizziness.

Eye Contact

Causes serious eye irritation.

Skin Contact

Causes skin irritation. Prolonged contact may cause redness and irritation. May cause skin irritation and/or dermatitis.

Ingestion

May cause irritation

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone	= 5800 mg/kg (Rat)	1700mg/kg (rabbit)	18892 mg/m ³
Toluene	>5580 mg/kg (Rat)	12124 mg/kg (Rat) 8390 mg/kg (Rabbit)	26700 ppm (Rat) 1 h
Xylene, mixed isomers	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 5000 ppm (Rat) 4 h = 47635 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization

No information available.

Mutagenic Effects

May cause genetic defects.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Toluene		Group 3	-	-
Xylene, mixed isomers		Group 3		
Silica, amorphous, precipitated and gel		Group 3		
Polyethylene		Group 3		
Carbon black	A3	Group 2B	-	X
Ethylbenzene	A3	Group 2B		X
Hexanoic acid, 2-ethyl-, cobalt(2+) salt (2:1)		Group 2B		X

IARC: (International Agency for Research on Cancer)

Group 3: Not Classifiable as to its Carcinogenicity to Humans

Reproductive Toxicity	May damage fertility or the unborn child
STOT - single exposure	No information available.
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration Hazard	May be fatal if swallowed and enters airways

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral	16321 mg/kg; Acute toxicity estimate
LD50 Dermal	22140 mg/kg; Acute toxicity estimate
Inhalation	
Vapor	166 mg/L; Acute toxicity estimate

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Harmful to aquatic life

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Acetone 67-64-1		LC50 96 h: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) LC50 96 h: 6210 - 8120 mg/L static (Pimephales promelas) LC50 96 h: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	EC50 48 h: 10294 - 17704 mg/L Static (Daphnia magna) EC50 48 h: 12600 - 12700 mg/L (Daphnia magna)
Toluene 108-88-3	EC50: >433 mg/L Pseudokirchneriella subcapitata 96 h EC50: 12.5 mg/L Pseudokirchneriella subcapitata 72 h static	LC50: 15.22-19.05 mg/L Pimephales promelas 96 h flow-through LC50: 12.6 mg/L Pimephales promelas 96 h static LC50: 5.89-7.81 mg/L Oncorhynchus mykiss 96 h flow-through LC50: 14.1-17.16 mg/L Oncorhynchus mykiss 96 h static LC50: 5.8 mg/L Oncorhynchus mykiss 96 h semi-static LC50: 11.0-15.0 mg/L Lepomis macrochirus 96 h static LC50: 54 mg/L Oryzias latipes 96 h static LC50: 28.2 mg/L Poecilia reticulata 96 h semi-static LC50: 50.87-70.34 mg/L Poecilia reticulata 96 h static	EC50 = 19.7 mg/L 30 min	EC50 48 h: 5.46 - 9.83 mg/L Static (Daphnia magna) EC50 48 h: = 11.5 mg/L (Daphnia magna)

Xylene, mixed isomers 1330-20-7	EC50 72 h: = 11 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 13.4 mg/L flow-through (Pimephales promelas) LC50 96 h: 2.661 - 4.093 mg/L static (Oncorhynchus mykiss) LC50 96 h: 13.5 - 17.3 mg/L (Oncorhynchus mykiss) LC50 96 h: 13.1 - 16.5 mg/L flow-through (Lepomis macrochirus) LC50 96 h: = 19 mg/L (Lepomis macrochirus) LC50 96 h: 7.711 - 9.591 mg/L static (Lepomis macrochirus) LC50 96 h: 23.53 - 29.97 mg/L static (Pimephales promelas) LC50 96 h: = 780 mg/L semi-static (Cyprinus carpio) LC50 96 h: > 780 mg/L (Cyprinus carpio) LC50 96 h: 30.26 - 40.75 mg/L static (Poecilia reticulata)		EC50 48 h: = 3.82 mg/L (water flea) LC50 48 h: = 0.6 mg/L (Gammarus lacustris)
------------------------------------	--	---	--	--

Persistence and Degradability No information available.

Bioaccumulation

Chemical Name	Log Pow
Acetone	-0.24
Petroleum gases, liquified, sweetened	2.8
Toluene	2.65
Xylene, mixed isomers	3.15
Propylene glycol monomethyl ether acetate	0.43
Ethylbenzene	3.118

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations

Contaminated Packaging Do not re-use empty containers.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone - 67-64-1		Included in waste stream: F039		U002
Toluene - 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
Xylene, mixed isomers - 1330-20-7		Included in waste stream: F039		U239
Component	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes

Toluene 108-88-3 (10-30)			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	
-------------------------------	--	--	--	--

14. TRANSPORT INFORMATION

DOT

Proper shipping name Consumer commodity
Hazard Class ORM-D
Reportable Quantity (RQ) Toluene: RQ kg= 2377.09, Xylenes isomers and mixture: RQ kg= 1842.23, Acetone: RQ kg= 7395.68
Description Consumer commodity, ORM-D
Emergency Response Guide Number 126

TDG

UN-Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Description UN1950, Aerosols, 2.1

MEX

UN-Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Description UN1950, Aerosols, 2.1

ICAO

UN-Number ID8000
Proper shipping name Consumer commodity
Hazard Class 9
Description ID8000, Consumer commodity, 9

IATA

UN-Number ID8000
Proper Shipping Name Consumer commodity
Hazard Class 9
ERG Code 9L
Description ID8000, Consumer commodity, 9

IMDG/IMO

UN-Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2
Subsidiary Class See SP63
EmS No. F-D, S-U
Description UN1950, Aerosols, 2.1 (See SP63)

RID

UN-Number	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2
Classification Code	5F
Description	UN1950, Aerosols, 2.1

ADR

UN-Number	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2
Classification Code	5F
Tunnel Restriction Code	(D)
Description	UN1950, Aerosols, 2.1, (D)
ADR/RID-Labels	2.1

ADN

Proper Shipping Name	Aerosols
Hazard Class	2
Classification Code	5F
Special Provisions	190, 327, 344, 625
Description	UN1950, Aerosols, 2.1
Limited Quantity	1 L
Ventilation	VE01, VE04

15. REGULATORY INFORMATION

International Inventories**Legend**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Toluene	108-88-3	10-30	1.0
Xylene, mixed isomers	1330-20-7	1-5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene	1000 lb	X	X	X
Xylene, mixed isomers	100 lb			X
1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich		X		
Ethylbenzene	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ

Acetone	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Toluene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Xylene, mixed isomers	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Toluene	108-88-3	Developmental
Carbon black	1333-86-4	Carcinogen
Ethylbenzene	100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Acetone	X	X	X		X
Toluene	X	X	X	X	X
Xylene, mixed isomers	X	X	X	X	X
Silica, amorphous, precipitated and gel	X	X	X		

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 4	Instability 1	Physical and Chemical Hazards -
HMIS	Health Hazard 2*	Flammability 4	Physical Hazard 1	Personal Protection X

*Indicates a chronic health hazard.

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 01-Feb-2017
Revision Date 01-Feb-2017
Revision Note Initial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet