

ROBECO / ASCOT PRODUCTS, Inc.

100 RING ROAD WEST - GARDEN CITY, NY 11530

[516] 248-1521 • FAX [516] 248-1524

REPORT #KGC35030;

Physical Property Data Sheet

KGC350

Lomenated

GAUGE:

30 MIL

FINISH:

DOUBLE POLISHED

HAND:

2.5\$

COLOR:

CLEAR

WIDTH:

VARIOUS

TENSILE STRENGTH:	MD	3600-3800 PSI
ASTM D-882		
	TD	2800-3300 PSI

ELONGATION: ASTM D-882	MD	305 - 355 %
	TD	315 - 385 %

100% MODULUS: ASTM D-882	MD	1,250 - 1,650 PSI
	TD	1,150 - 1,550 PSI

GRAVES TEAR: ASTM D-1004	MD	380-420 LBS./IN.	The state of the s
	TD	370-410 LBS./IN.	-

	T	
UV/CON	1000 HRS.	NO SIGNIFICANT CHANGE IN COLOR

FILM CHARACTERISTICS:

FORMULATED WITH UV INHIBITOR

This information is, to the best of the company's knowledge, accurate under numerous conditions; however, it does not apply in all cases. The summary chat is intended only as a guideline and all recommendations are made without guarantee since conditions of use are beyond our control.